

HI-5133

Main Features

1/3" SONY CCD With Housing
 520 TV line 0.1 Lux/F2.0 / IP65
 LED 91 pcs. 0 Lux 40M IR On
 Lens 4,6,8 mm. Day& Night
 more than 48 dB,(ATW, BLC Auto)
 Power AC 110V-240V



Specifications

Model	HV-5133-V
Image Device	1/3" Sony CCD sensor
Scanning Frequency	NTSC: 15,734KHz(H), 60Hz(V); PAL: 15,625KHz(H),50Hz(V)
Scanning System	NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace
Effective Pixels	NTSC: 512(H) x 492(V); PAL:512(H) x 582(V)
Electronic Shutter	N:1/60- 1/100,000 sec (Auto); PAL:1/50-1/100,000sec (Auto)
Horizontal	520 TV Lines
White-balance	Auto white balance (2500 °K~9500 °K)
Synchronizing System	Internal
Sensitivity	0.1 Lux , 0 Lux at IR on / F2.0
BLC	Auto
Signal to Noise	More than 48dB AGC off
AGC	Yes
Gamma Correction	0.45
IR Distance	40 Meters (Max.)
IR LED	91 pcs LED
IR Status	Under 10 Lux by CDS auto control
IR View Angle	View angle: 70 ° Beam spread: 40 °/per LED
IR Wavelength	850nm - 25nm
LED Life	More than 10,000 hours
Lens	6mm lens (4,8 12 mm Option)
Power Consumption	IR on: 1A, IR off: 70mA +- 5mA
Power Supply	110V ~ 240AC
Temperature	Operating: -10 to 50 °C
Video Output	Composite 1.0 Vp-p at 75 ohm
Construction	Aluminum
Dimensions	124(w)x115(H) x300(L) mm